



Embargo Date: 19th August 2009
Sales Start Date: 26th August 2009
Target Market: Advanced / Home / Office

Key Features in Importance Order:

- Advanced Wi-Fi home photo All-In-One with 5 Single Inks
- Canon uses ISO standard for realistic print speeds, document ESAT speed 9.2ipm mono, 6ipm colour
- 9600x2400dpi 1pl for superior photolab-quality: 10x15cm borderless photo in approx. 39sec*
- Smart & simple interface; 5cm TFT display and Easy-Scroll Wheel
- Auto duplex, 2-way paper feed
- 2400dpi scanner for high quality scanning & copying
- Print photos directly via PictBridge, memory cards or optional Bluetooth
- Easy-WebPrint EX to easily clip, combine, edit and print from the web
- Auto Photo Fix II corrects and enhances photos
- ChromaLife100+ for longer lasting, beautiful photos**

* See specifications

** See www.canon-europe.com/chromalife100

Premium quality All-In-One with the convenience of wireless connectivity.

The PIXMA MP560 is an advanced photo All-In-One designed for homes and small offices. With built-in Wi-Fi, auto duplex printing and 5 Single Ink tanks, stunning quality combines with versatility.

The PIXMA MP560 is part of the PIXMA Photo All-In-One range.

The PIXMA Photo All-In-One range consists of: PIXMA MP990, PIXMA MP640, **PIXMA MP560**, PIXMA MP490, PIXMA MP270

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA MP560	3747B008AA	4960999638478	£149.00

What's in the box: PIXMA MP560 All-In-One, power cord, print head, ink tanks (PGI-520BK, CLI-521C, CLI-521M, CLI-521Y, CLI-521BK), multilingual set-up guides, set-up software & user manual CD (including MP Navigator EX, Easy-PhotoPrint EX, Easy-WebPrint EX downloader), warranty sheet, photo paper range leaflet

Consumables	Mercury Code	EAN Code	Recommended Retail Price
PGI-520BK	2932B001AA	4960999577456	£8.99
CLI-521BK	2933B001AA	4960999577470	£7.99
CLI-521C	2934B001AA	4960999577494	£7.99
CLI-521M	2935B001AA	4960999577517	£7.99
CLI-521Y	2936B001AA	4960999577531	£7.99

Note: Blister packs with and without security are available for each of the inks listed above

Technical Specifications

TYPE Available Functions	Wi-Fi ready Premium All-In-One Photo Printer with Auto Duplex print Easy-Scroll Wheel and 5cm (2") colour TFT display.
PRINTER FUNCTIONS Print Resolution Print Engine Photo Lab Quality Speed Mono Print Speed Colour Print Speed Ink Cartridge Configuration Black Ink Tank Life Colour Ink Tank Life Media Type Media Input Media Size Media Weight Two Sided Printing Borderless Printing Camera Interface and Connectivity Card Direct Printing	Up to 9600 ¹ x 2400 dpi InkJet 5-ink with minimum 1 pl droplet size, FINE print head and ContrastPLUS Borderless 10 x 15cm: Approx. 39 seconds (Standard) ESAT: Approx. 9.2 ipm ESAT: Approx. 6.0 ipm Single Ink technology - 5 separate ink tanks (PGI-520BK, CLI-521BK, CLI-521C, CLI-521M, CLI-521Y) Black: 324 pages (PGI-520BK), 3425 pages* (CLI-521BK) ² Black: 4080 photos* (PGI-520BK), 650 photos* (CLI-521BK) ³ *Estimated Supplemental Yield Cyan: 535 pages (CLI-521C), Magenta: 510 pages (CLI-521M), Yellow: 530 pages (CLI-521Y) ² Cyan: 203 photos (CLI-521C), Magenta: 193 photos (CLI-521M), Yellow: 206 photos (CLI-521Y) ³ Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101) Rear Tray: Max. 150 sheets Cassette: Max. 150 sheets Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm Cassette: A4, B5, A5, Letter Rear Tray: Plain paper: 64 to 105 g/m ² and supported Canon special media up to 300 g/m ² Cassette: Plain paper: 64 to 105 g/m ² Automatically selectable using plain paper in A4, B5, A5 & Letter sizes Yes (A4, Letter, 20 x 25cm, 13 x 18cm, 10 x 15cm) Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders USB Flash Memory, CompactFlash, Microdrive, Memory Stick, Memory Stick Pro, Memory Stick Duo, Memory Stick PRO Duo, SD Memory Card, SDHC Memory Card, MultiMedia Card (Ver4.1), and MultiMedia Card Plus (Ver4.1). xD-PictureCard ⁴ , xD-PictureCard Type M ⁴ , xD-PictureCard Type H ⁴ , Memory Stick Micro ⁴ , RS-MMC ⁴ , mini SD Card ⁴ , micro SD ⁴ , mini SDHC Card ⁴ and micro SDHC ⁴ .
SCANNER FUNCTIONS Scanner Type Scanner Resolution Optical Scanner Resolution Digital Colour Scanning Depth Halftone/Greyscale Compatibility Effective Scanning Width OCR Bundle Other Features	Flatbed CIS colour scanner Up to 2400 x 4800dpi Up to 19200 x 19200dpi 48 / 24 bit (RGB each 16 / 8 bit) 16 / 8 bit TWAIN / WIA (Windows XP/Windows Vista) A4/LTR Yes (MP Navigator EX) Push-scan, Auto Scan Mode, Scan to USB stick, Scan to memory card, Multi-Scan, PDF file creation/editing/password security*, Descreen, Unsharp mask, Stitch Assist*, Correct document orientation, Prevent show through, Correct slanted documents, Photograph corrections (Fading correction, Grain correction, Reduce dust and scratches, Backlight correction, Auto Tone), Gutter Shadow Correction, Text (OCR) * Function with MP Navigator EX
COPIER FUNCTIONS Colour/Photo Copy Copy Speed Colour Document Multiple Copy Zoom	Yes FCOT: Approx. 26 secs. max.99 copies 25 - 400% in 1% increments and preset ratios

COPIER FUNCTIONS (continued) Other Features	Auto Intensity (AE copy), Manual Intensity Adjustment, Image Repeat copy, Fit-to-page copy, Borderless copy, Sticker copy, 2-on-1 copy, 4-on-1 copy, Frame Erase copy, Shadow erase, Trimming/Masking copy, Photo reprint, Face brightener, Fade restoration, Manual colour adjustment (brightness/contrast/hue), Gutter shadow corrected copy, Auto Photo Fix II
INTERFACE AND SOFTWARE Interface Type - PC Interface Type - Mobile Phone / PDA Supported Operating System Software Included	Hi-Speed USB (B Port), Bluetooth Ver2.0 maximum speed 1.44Mbps (Option, HCRP) (with optional Bluetooth Unit BU-30) Wi-Fi: IEEE802.11g/IEEE802.11b (Compatible with IEEE802.11n ⁵), Frequency: 2.412GHz-2.472GHz, Set-up: WCN, WPS (Push-Button Configuration, PIN code method), Security: WPA-PSK, WPA2-PSK, WEP64/128bit, Administration password Bluetooth Ver2.0 maximum speed 1.44Mbps (Option, JPEG only, OPP, BIP) (with optional Bluetooth unit BU-30) Photo printing via PictBridge Windows Vista, Vista SP1 / Windows XP SP2, SP3 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5 Canon MP Navigator EX, Canon Easy-PhotoPrint EX, Canon Easy-WebPrint EX*, *Canon Easy-WebPrint EX available as download from www.canon-europe.com , Internet Explorer 7 or later is required
GENERAL FEATURES Dimensions (W x D x H) Number of language (LCD) Temperature Range Humidity Acoustic Noise Levels Weight Power Source Power Consumption	453 x 368 x 160mm 22 Languages selectable Operating environment: 5° - 35° C Operating humidity: 10 - 90%RH (no condensation) Printing (when feeding from rear tray): Approx. 44.5 dB(A) When printing ISO/JIS-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using default settings Approx. 8.1 kg AC 100-240V, 50/60Hz Standby: Approx. 1.9W (when scanning lamp is off), Off: Approx. 0.5W, Copying: Approx 14W ⁶

All specifications subject to change without notice.

Borderless 10x15cm photo lab quality print speed based on default driver setting using ISO/JIS-SCID N2 on Canon Photo Paper Plus Glossy II media

Document print speed (ipm) on plain paper is measured based on the office category test of ISO/IEC 24734.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used and does not take into account data processing time on host computer.

FCOT on plain paper is measured based on the test standard of ISO/IEC 24735 Annex D. ESAT ADF copy speed on plain paper is measured based on the test standard of ISO/IEC 24735.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield
All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

For more information on ChromaLife100+ please visit www.canon-europe.com/chromalife100

¹ Ink droplets can be placed with a minimum pitch of 1/9600 inch

² Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.

³ Printing Canon standard photos continuously on 10x15cm Photo Paper Plus Glossy II with default settings using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery. Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.

⁴ Using recommended adapter - not supplied

⁵ Transmission rate will be limited to IEEE802.11g and operate in the 2.4GHz frequency band.

⁶ When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.