

PJD6211

Versatile, Portable XGA DLP Projector

120HZ, 3D-READY

Price/performance leader in portable DLP projectors.

ViewSonic's PJD6211 DLP® projector is ideal for use in the office or on the road. It delivers amazingly clear images with the digital clarity of DLP's BrilliantColor™ technology. This budget-friendly projector boasts amazingly fast 120Hz frame rate and is 3D ready for commercial 3D applications and 3D games at home. With high contrast ratio, brightness and ViewMatch™ technology to adjust colors perfectly, your presentations will be rich, vibrant regardless of the setting. Multiple preset presentation modes, an increased ±40 degree digital keystone correction and powerful 1.2x optical zoom ensure the best possible image regardless of location. With up to 5000 hours of lamp life, low cost replacement lamps, filter-less design and a non-degrading DLP light engine, the PJD6211 has one of the best "TOTAL COST OF PROJECTION" ratios in the industry.



OUTSTANDING PRESENTATIONS

- > **Bright in virtually any setting**
Packs 2300 ANSI lumens in just 2.6kgs, and with a high 2000:1 contrast ratio (typ), your presentations are guaranteed to be vibrant even in the brightest office environment.
- > **BrilliantColor™ technology**
Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.
- > **Low total cost of ownership**
Make the most of your projector investment with long life lamps with up to 5000 hours lamp life and a filter-less dust resistant design that reduces maintenance costs.
- > **Protect your investment**
Assign a PIN code to password protect the projector from unauthorized use or theft.
- > **The perfect setup convenience**
The automatic vertical keystone correction (+/- 40 degrees), aspect ratio adjustment and powerful 1.2x optical zoom ensures a perfect image in any room. Adjustable feet let you adjust the image at even higher viewing angles.
- > **Industry leading warranty**
Enjoy full peace of mind with a generous 3 years on-site product warranty and a limited one year lamp warranty.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

PJD6211

Versatile, Portable XGA DLP Projector

ViewSonic®
See the difference™ 

Model No.VS12618



Optional Accessories

| | |
|-------------------------------------|-------------|
| Replacement lamp | RLC-050 |
| Wireless presentation gateway | WPG-350 |
| Universal Ceiling Mount | WMK-018 |
| Extended 3-year lamp warranty | LSWPY3 |
| Universal soft case | PJ-CASE-001 |

| Projection Distance | | 4:3 Screen Screen Size | | | |
|---------------------|-------|------------------------|--------|------|------|
| | | Wide | | Tele | |
| M | feet | m | inch | m | inch |
| 1.5 | 4.92 | 0.99 | 38.85 | 0.89 | 35 |
| 1.8 | 5.90 | 1.18 | 46.62 | 1.07 | 42 |
| 2 | 6.56 | 1.32 | 51.80 | 1.19 | 47 |
| 3 | 9.84 | 1.97 | 77.70 | 1.79 | 70 |
| 5 | 16.40 | 3.29 | 129.51 | 2.98 | 117 |
| 10 | 32.80 | 6.58 | 259.01 | 5.95 | 234 |



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

| | | |
|-------------------------------|--------------------|--|
| DISPLAY | Type | 0.55" Digital Micromirror Device (DLP™) |
| | Resolution | XGA 1024×768 (Native) / SXGA 1280×1024 (compressed) |
| | Lens | 1.2× Manual optical zoom/ Manual optical focus |
| | Keystone | Vertical digital keystone correction: ± 40 degrees |
| | Size | 27" -300" |
| | Throw Distance | 1.2m-10m |
| | Throw Ratio | 1.6:1-1.9:1 |
| | Lamp | 180watt (RLC-050) |
| | Lamp Life | 4000 / 5000 hrs |
| | Brightness | 2,300 Lumens |
| | Contrast Ratio | 2000:1 (with DCR) |
| | Aspect Ratio | 4:3 & 16:9 |
| | Color Depth | 24 bits, 16.7M Colors (8+8+8) |
| | Color Wheel | 6-Seg RGBCYW / 7200rpm |
| Color Gamut | 85 % NTSC 1931 CIE | |
| AUDIO | Speaker | 2W x 1 |
| INPUT SIGNAL | Computer and video | NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps) |
| | Frequency | Fh: 31-100 KHz, Fv: 50-120 Hz |
| COMPATIBILITY | PC | VGA to SXGA |
| | Mac | Up to 1024×768 (may require Mac Adapter) |
| CONNECTOR | RGB Input | 2 × 15-pin mini D-sub |
| | RGB Output | 1 × 15-pin mini D-sub |
| | Composite Input | 1 × RCA jack |
| | S-Video Input | 1 × 4-pin mini-DIN |
| | Audio Input | 1 × 3.5mm mini jack |
| | Audio Output | 1 × 3.5mm mini jack |
| | Control | 1 × RS-232 (9 Pin D-sub) |
| | USB | 1 × type B |
| POWER | Voltage | 90~240VAC(Auto Switching), 50/60Hz (universal) |
| | Consumption | 235W (Typical) / <1W (Stand-by mode) |
| LANGUAGE | | English / Dutch / French / Spanish / Italian / Korean / Thai / Portuguese / T. Chines / S. Chinese / Japanese / Russian / German / Swedish / Turkish / Finnish / Polish |
| CONTROLS | Basic | POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key lock, AUTO, MODE/ENTER, SOURCE |
| | OSD | Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert. Computer Image: Frequency, Tracking, H Position, V Position Video Image: Saturation, Sharpnes, Tint Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter Hours Reset,Power Saving, Auto Source, ECO Mode, High Altitude, OSD Timeout Advance: Blank Screen, Password Word, Screen Capture, Start up Screen, Text Shot: Digital Zoom, DCR, Close Captions, Brilliant Color |
| OPERATING CONDITION | Temperature | 0°C-40°C (32°F-104°F) |
| | Humidity | 10%-90% (non-condensing) |
| | Altitude | 0~6,000 ft (1,800 m), operational up to 10,000 ft (3048 m) at reduced reliability and performance |
| NOISE LEVEL | Normal/ Eco Mode | 31dB/ 29dB |
| DIMENSIONS (W x D x H) | Physical | 280 x 114 x 218 (mm) / 11 x 4.25 x 8.58 (in) |
| WEIGHT | Net | 2.6 kg (5.7 lb) |
| REGULATIONS | | CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC |
| WARRANTY | | 3-year limited warranty on parts, 1-year limited warranty on lamp |

Rev.1.0

ViewSonic Europe Limited/UK
Tower 42
25 Old Broad Street
London EC2N 1HQ
United Kingdom

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

| | |
|-------------------|----------------------------|
| ViewSonic Benelux | Tel: +31 (0)20 491 9254 |
| ViewSonic Denmark | Tel: +45 70 22 11 71 |
| ViewSonic Finland | Tel: +358 (0)20 7120 860 |
| ViewSonic MEA | Tel: +971 (0) 4 88 11 871 |
| ViewSonic Norway | Tel: +47 (0) 22 88 17 60 |
| ViewSonic Spain | Tel: +34 (0) 91 63 05 339 |
| ViewSonic Sweden | Tel: +46 (0) 8 50 71 30 00 |

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD6211

For more product information, visit us on the web at viewsoniceurope.com